

Litezupp Headlamp Data Sheet

Globe options:

L5NP-H43G - 5 3/4" ROUND CRYSTAL CLEAR GLASS LENS / METAL HOUSING HEADLAMP

L5C-H43G – 5 3/4" INCH ROUND CLASSIC FLUTED GLASS LENS / METAL HOUSING HEADLAMP

L7NP-H43G - 7" INCH ROUND CRYSTAL CLEAR GLASS LENS / METAL HOUSING HEADLAMP

L7C-H43G R – 7" INCH ROUND CLASSIC FLUTED GLASS LENS / METAL HOUSING Offered
Traditional Round 4" depth

L7C-H43G S – 7" INCH ROUND CLASSIC FLUTED GLASS LENS / METAL HOUSING
Flatter globe 3.25" depth (best for smaller buckets)

Clear Lens

or

Classic Fluted Lens in two styles

*R style
5/8" curve
4" deep*

*S style
3/8" curve
3.25" deep*



- New PAIR (2) Headlamps with (2) High Intensity 3rd Generation Led H4 Intense White LED Bulbs!
- Daylight White Brightness
- 360° Light Beam Angle
- High & Low Beam Function works with factory wiring
- Original 3 Prong Plug Design (Plug & Play)
- High Quality Glass Faced & Metal Backed
- Semi-Sealed Beam - Removable / Replaceable Light Bulbs (H4)
- Fits cars and trucks with 5 3/4" (L5NP-H43G) or 7" (L7NP-H43G or L7C-H43G) round headlights
- Plug and Play Fitment into stock bucket – min ~4.25" depth L7C Round or ~3.5" L7C Flat
- Negative ground or Positive Ground systems



Sealed beam Halogen Bright



Litezupp L7NP LED Bright

LED LIGHT BULB

Specifications and Features:

- H4 configuration
- 3000 Lumen Light Output Per Bulb – 300% more than Halogen
- 360 Degree Light Beam Angle/ 4 sides
- Beam pattern consistent with older Filament bulbs
- Power: about 25-30w Watts
- Beam Energy - 50% more efficient than Halogen
- Input Voltage: 9-36V DC
- Working voltage: 12V DC
- LED Light Color: 6,000K- 6500K
- Waterproof Ball-Bearing Fan for cooling
- LED Protection Circuit to protect from reverse polarity, low voltage or high voltage spikes.
- Smart and Efficient Cooling System uses aluminum radiator and built-In Cooling Fan.
- Greater Visibility - 3 times brighter than factory halogen bulbs.
- High quality Aluminum heat sink ensures proper temperature regulation.
- Lower Power Consumption than Halogen bulb.
- Vibration proof design.
- 30,000 Hour Lifespan
- Easy installation, Plug and Play, No modification required
- No Splicing of harnesses required for LED bulbs
- OBC Error free operation
- Negative ground or Positive ground systems



Connector pinout:

